

JANTZEN AUDIO

Center 8008 mk II

Designed by Troels Gravesen

Page 1: Crossover component overview and kit level comparison

Page 2: Damping materials and accessories overview

BASICS

Speaker type:

3-way

Cabinet:

65 x 36 x 28 cm, WxDxH.

System sensitivity:

92 dB/2.8V/1 meter.

Impedance:

4-8 Ohms.

Power requirement:

30+ watts/channel.

Level 1 - Crossover component overview:



Level 1 kit comes with a higher grade of capacitors compared to level 2 kit



Air core wire coils



Tweeter capacitors: Superior Z-Caps (Super MKP)



Midrange / bass capacitors: Superior Z-Caps (Super MKP)



Superes wire-wound resistors



Level 2 - Crossover component overview:

Coils and resistors are indential to level 1 kit



Tweeter capacitors: Standard Z-Caps (MKP)



Midrange / bass capacitors: Standard Z-Caps (MKP)



Damping materials included:

Grey damping felt



White polyester damping cloth:



Accessories included:

Binding post terminals (2 pairs)



Port tubes (bass reflex ports)




16 AWG PFTE insulated silver infused cables (for internal wiring)



Sodler tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

