

ATS4-HE

Designed by Troels Gravesen

Page 1: Crossover component overview and kit level comparison

Page 2: Damping materials and accessories overview

BASICS

Speaker type:

4-way

System sensitivity:

92 dB/2.8V, 1 meter.

Impedance:

8 Ohm, 4.4 Ohm minimum at 325 Hz for the MT section

Power requirement:

25+ wpc for the MT section.
+ Hypex FA252 for bass

Level 1 - Crossover component overview:



Level 1 kit comes with upgraded midrange capacitors compared to level 2 kit



Wax Coils (foil-based coils)



Air core wire coils



Tweeter capacitors: Alumen Z-Caps (Pure aluminum foil)



Midrange capacitors: Alumen Z and Superior Z-Caps



Superes wire-wound resistors



Level 2 - Crossover component overview:

Coils and resistors are identical to level 1



Tweeter capacitors: Alumen Z-Caps (Pure aluminum foil)



Midrange capacitors: Superior Z-Caps (Super MKP)



Damping materials included:

Grey damping felt



White polyester damping cloth



Combed natural wool stuffing



Accessories included:

Binding post terminals (4 pairs)



Straight port set (bass reflex)



16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



Screw-in terminals



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

