

Bookshelf 3WC

Designed by Troels Gravesen

Page 1: Crossover component overview and kit level comparison

Page 2: Damping materials and accessories overview

BASICS

Speaker type:

3-way

Cabinet:

45 x 30 x 28 cm (WxDxH)

System sensitivity:

90 dB/2.8V/1 meter.

Impedance:

8 Ohms, minimum 3.3 Ohms
@ 125 Hz.

Power requirement:

20+ wpc.

Level 1 - Crossover component overview:

 **Level 1 kit has higher grade of tweeter/midrange capacitors compared to level 2** 

Air core wire coils



Iron core wire coils




Tweeter capacitors: Superior Z-Caps (Super MKP)



Midrange capacitors: Superior Z-Caps (Super MKP)



Bass capacitors: Cross Caps & Compact MKT caps



Superes wire-wound resistors



Level 2 - Crossover component overview:

Coils, bass capacitors and resistors are identical to level 1 

Tweeter capacitors: Standard Z-Caps (MKP)



Midrange capacitors: Standard Z-Caps (MKP)



Damping materials included:

Grey damping felt



White polyester damping cloth:



Accessories included:

Binding post terminals (2 pairs)



16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

