

# JANTZEN AUDIO

## Purifi 6661 (Passive)

Designed by Troels Gravesen

**Page 1:** Crossover component overview and kit level comparison

**Page 2:** Damping materials and accessories overview

### BASICS

**Speaker type:**

3-way

**Cabinet:**

25 x 38 x 100 cm, WxDxH.

Height 105-107 cm with feet.

**System sensitivity:**

90 dB/2.8V/1 meter.

**Impedance:**

4-8 Ohms

**Power requirement:**

50+ watts/channel.

### Level 1 - Crossover component overview:



Level 1 kit has a higher grade tweeter capacitors compared to level 2 kit



Litz wire wax coils



C-Coils (Toroidal core)



Air & iron core wire coils



**Tweeter capacitors:** Amber Z-Caps (Pure copper foil)




**Midrange capacitors:** Silver Z-Caps (Super MKP)



**Bass capacitors:** Cross Caps



Superes wire-wound resistors



### Level 2 - Crossover component overview:

Coils, midrange/bass capacitors and resistors are identical to level 1



**Tweeter capacitors:** Alumen Z-Caps (Pure aluminum foil)



## Damping materials included:

Grey damping felt



White polyester damping cloth



Combed natural wool stuffing



## Accessories included:

Binding post terminals (4 pairs)



90° angled port set (bass reflex)




16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

