

JANTZEN AUDIO

SBA 861 PFCR

Designed by Troels Gravesen

Page 1: Crossover component overview and kit level comparison

Page 2: Damping materials and accessories overview

BASICS

Speaker type:

3-way

Cabinet:

25 x 28 x 105 cm, WxDxH
(H +30 mm for feet to allow
free ventilation from port).

System sensitivity:

91-92 dB/2.8V/1 meter.

Impedance:

4-8 Ohms.

Power requirement:

20+ wpc.

Level 1 - Crossover component overview:

 **Level 1 kit has higher grade of tweeter capacitors compared to level 2** 


Air core wire coils



Tweeter capacitors: Superior Z-Caps & Electrolytic caps




Midrange capacitors: Standard Z-Caps & Cross Caps



Bass capacitors: Cross Caps & Electrolytic caps



MOX resistors



Level 2 - Crossover component overview:

Coils, midrange / bass capacitors and resistors are identical to level 1



Tweeter capacitors: Cross Caps & Electrolytic caps



Damping materials included:

Grey damping felt



White polyester damping cloth:



Accessories included:

Binding post terminals (2 pairs)



Cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

