

# JANTZEN AUDIO

## SBA MW19 Monitor (Fabric)

Designed by Troels Gravesen

Page 1: Crossover component and kit level comparison

Page 2: Damping materials and accessories overview

### BASICS

**Speaker type:**

2-way

**System sensitivity:**

88 dB/2.8V, 1 meter.

**Impedance:**

8 Ohms.

Minimum 6.2 Ohms @ 150 Hz.

**Power requirement:**

Minimum 20 wpc.

### Level 1 - Crossover component overview:



Level 1 kit has higher grade tweeter capacitors compared to level 2



Cross Coils (foil-based coils)



Air & Iron core wire coils



**Tweeter capacitors:** Alumen Z-Caps (Pure aluminum foil)



**Midrange / bass capacitors:** Superior Z-Caps (Super MKP)



Superes wire-wound resistors



### Level 2 - Crossover component overview:

Coils, midrange / bass capacitors and resistors are identical to level 1



**Tweeter capacitors:** Superior Z-Caps (Super MKP)



## Damping materials included:

Grey damping felt



White polyester damping cloth



## Accessories included:

Binding post terminals (2 pairs)



Port tubes (bass reflex)




16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

