

JANTZEN AUDIO

SEAS 3WC mk II

Designed by Troels Gravesen

Page 1: Crossover component overview and kit level comparison

Page 2: Damping materials and accessories overview

BASICS

Speaker type:

3-way

System sensitivity:

90-91 dB/2.8V, 1 meter.

Impedance:

8 Ohms.

4 Ohms minimum @ 800 Hz

Power requirement:

10+ wpc.



Level 1 - Crossover component overview:



Level 1 kit comes with higher grade tweeter/midrange capacitors compared to level 2

Air core wire coils



Iron core wire coils



Tweeter capacitors: Superior Z-Caps (Super MKP)



Midrange capacitors: Superior Z-Caps (Super MKP)



Bass capacitors: Cross Caps



Superes wire-wound resistors



Level 2 - Crossover component overview:

Coils, bass capacitors and resistors are identical to level 1



Tweeter capacitors: Standard Z-Caps (MKP)



Midrange capacitors: Standard Z-Caps (MKP)



Damping materials included:

Grey damping felt



White polyester damping cloth:



Accessories included:

Binding post terminals (2 pairs)



Port tubes (bass reflex)



16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

