

JANTZEN AUDIO

eleCap 5%

ALUMINUM ELECTROLYTIC CAPACITOR



PRODUCT FEATURE

The Jantzen eleCap 5%, is a standard-type aluminum electrolytic capacitor, using etched or “raw” foil.

With a low tolerance of only +/- 5% on capacity, it is a more precise capacitor than most other standard-type electrolytic capacitors that usually have a tolerance of +/-10% on capacity.

Being both price friendly and versatile, this capacitor is both a sensible choice for bass section application, but also when limited space on the crossover calls for a very small capacitor.

TECHNICAL DATA (Part 1 of 2)

- Capacitor foil: Aluminum electrolytic
- Voltage rating: 100 VDC / 35 VAC
- Capacity tolerance: +/- **5%** (on nominal value)
- Capacity change rate: Less or equal to 10%
- Temperature range: - 40C to + 85C
- Leakage current: 33 μ A @ 10 μ F
- Signal direction: non-polarized (bi-polar capacitor)

TECHNICAL DATA (Part 2 of 2)

Capacity (uF):	DF (Max):	@Frequency	ESR Max. Ω	Size (mm):	Weight (kg):
1	<0,10	1 kHz	15,92	8*17	0,002
1,5	<0,10	1 kHz	10,62	8*17	0,002
2,2	<0,10	1 kHz	7,24	8*17	0,002
2,7	<0,10	1 kHz	5,90	8*17	0,002
3,3	<0,10	1 kHz	4,83	8*17	0,002
3,9	<0,10	1 kHz	4,08	8*19	0,002
4,7	<0,10	1 kHz	3,39	8*19	0,002
5,6	<0,10	1 kHz	2,84	10*19	0,002
6,8	<0,10	1 kHz	2,34	10*19	0,002
8,2	<0,10	1 kHz	1,94	10*19	0,002
10	<0,10	1 kHz	1,59	10*19	0,002
12	<0,10	1 kHz	1,33	10*19	0,002
15	<0,10	1 kHz	1,06	10*19	0,002
18	<0,10	1 kHz	0,88	10*24	0,003
22	<0,10	1 kHz	0,72	10*24	0,003
27	<0,10	1 kHz	0,59	13*27	0,005
33	<0,10	1 kHz	0,48	13*27	0,005
39	<0,10	1 kHz	0,41	13*32	0,005
47	<0,10	1 kHz	0,34	13*32	0,006
56	<0,10	1 kHz	0,28	13*32	0,006
68	<0,10	1 kHz	0,23	13*32	0,006
82	<0,10	1 kHz	0,19	16*34	0,009
100	<0,10	1 kHz	0,16	16*34	0,009
120	<0,10	1 kHz	0,13	16*34	0,009
150	<0,10	1 kHz	0,11	16*34	0,009
220	<0,10	1 kHz	0,07	16*43	0,011
270	<0,10	1 kHz	0,06	18*44	0,017
300	<0,10	1 kHz	0,05	22*45	0,021
330	<0,10	1 KHz	0,05	22*45	0,022
470	<0,10	120 Hz	0,28	22*45	0,025
560	<0,10	120 Hz	0,24	25*52	0,034
820	<0,10	120 Hz	0,16	25*52	0,035

VALUES AND PRODUCT INDEXES

- 1,00 μ F (Product Index: 001-6105)
- 1,50 μ F (Product Index: 001-6108)
- 2,20 μ F (Product Index: 001-6111)
- 2,70 μ F (Product Index: 001-6114)
- 3,30 μ F (Product Index: 001-6117)
- 3,90 μ F (Product Index: 001-6120)
- 4,70 μ F (Product Index: 001-6123)
- 5,60 μ F (Product Index: 001-6126)
- 6,80 μ F (Product Index: 001-6129)
- 8,20 μ F (Product Index: 001-6132)
- 10,00 μ F (Product Index: 001-6135)
- 12,00 μ F (Product Index: 001-6138)
- 15,00 μ F (Product Index: 001-6141)
- 18,00 μ F (Product Index: 001-6144)
- 22,00 μ F (Product Index: 001-6147)
- 27,00 μ F (Product Index: 001-6150)
- 33,00 μ F (Product Index: 001-6153)
- 39,00 μ F (Product Index: 001-6156)

VALUES AND PRODUCT INDEXES

- ▶ 47,00 μ F (Product Index: 001-6159)
- ▶ 56,00 μ F (Product Index: 001-6162)
- ▶ 68,00 μ F (Product Index: 001-6165)
- ▶ 82,00 μ F (Product Index: 001-6168)
- ▶ 100,00 μ F (Product Index: 001-6171)
- ▶ 120,00 μ F (Product Index: 001-6174)
- ▶ 150,00 μ F (Product Index: 001-6177)
- ▶ 220,00 μ F (Product Index: 001-6180)
- ▶ 270,00 μ F (Product Index: 001-6183)
- ▶ 300,00 μ F (Product Index: 001-6186)
- ▶ 330,00 μ F (Product Index: 001-6189)
- ▶ 470,00 μ F (Product Index: 001-6192)
- ▶ 560,00 μ F (Product Index: 001-6195)
- ▶ 820,00 μ F (Product Index: 001-6198)